

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 September 2005 (09.09.2005)

PCT

(10) International Publication Number
WO 2005/083822 A1

(51) International Patent Classification⁷: **H01M 8/04**,
8/06, 4/94

(21) International Application Number:
PCT/JP2005/002970

(22) International Filing Date: 17 February 2005 (17.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-051445 26 February 2004 (26.02.2004) JP

(71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA** [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **OGINO, Shigeru** [JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). **AOYAMA, Satoshi** [JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI


KAISHA, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). **IZAWA, Yasuhiro** [JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). **SHIOKAWA, Satoshi** [JP/JP]; c/o KABUSHIKI KAISHA INTER PROJECT, Aioison-poshizuokadaichibilu 2F, 3-1, Sakae-cho, Shizuoka-shi, Shizuoka 4200859 (JP). **SHIMAZU, Takashi** [JP/JP]; c/o KABUSHIKI KAISHA TOYOTA CHUO KENKYUSHO, 41-1, Aza Yokomichi, Oaza Nagakute, Nagakute-cho, Aichigun, Aichi 4801192 (JP). **AOKI, Hiroshi** [JP/JP]; c/o KABUSHIKI KAISHA TOYOTA CHUO KENKYUSHO, 41-1, Aza Yokomichi, Oaza Nagakute, Nagakute-cho, Aichigun, Aichi 4801192 (JP). **MITSUMI, Hiroyuki** [JP/JP]; c/o KABUSHIKI KAISHA TOYOTA CHUO KENKYUSHO, 41-1, Aza Yokomichi, Oaza Nagakute, Nagakute-cho, Aichigun, Aichi 4801192 (JP).

(74) Agent: **TOKKYO GYOMUHOJIN MEISEI INTERNATIONAL PATENT FIRM**; Mitsui-Sumitomo Bank Bldg., 7th floor, 18-19, Nishiki 2-chome, Naka-ku, Nagoya-shi, Aichi 4600003 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

[Continued on next page]

(54) Title: FUEL CELL SYSTEM



(57) Abstract: A technology for preventing degradation of a hydrogen permeable metal layer in a fuel cell 210 is provided. A fuel cell system 200 including a fuel cell 210 with an anode which has the hydrogen permeable metal layer comprises a fuel cell controller 230 for controlling the operation status of the fuel cell system 200, a temperature parameter acquisition section for acquiring a temperature parameter of the hydrogen permeable metal layer, and a hydrogen permeable metal layer degradation prevention section which reduces the hydrogen partial pressure in an anode channel 212 for supplying fuel gas to the anode. If a temperature of the hydrogen permeable metal layer represented by the temperature parameter deviates from a specified temperature range, the fuel cell controller 230 cause the hydrogen permeable metal layer degradation prevention section to operate for preventing degradation of the hydrogen permeable metal layer.

WO 2005/083822 A1



AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.